



AX-930

802.11ax (4X4) PCI Express Mini Card



The AX-930 with Qualcomm® 802.11ax technology is a highly integrated wireless local area network (WLAN) system-on-chip (SoC) and is equipped with PCI Express 3.0 interface and M.2 E key slot. The AX-930 performs AP and STA functionality with 4x4 MIMO and 4 spatial streams. Apart from slower traffic, it also enables Dynamic Frequency Selection (DFS) function to help devices avoid radars (on the same frequency).

Hardware	Standards	IEEE 802.11ax
	Host Interface	PCI Express 3.0 interface, M.2 E-key
	Operating Voltage	3.3V/5V
	Operating Frequency	5G: 5.180GHz~5.850GHz
	Modulation	802.11n: OFDM (BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM) 802.11ac: OFDM (BPSK, QPSK, 16-QAM, 64-QAM, 256-QAM) 802.11ax: OFDMA (BPSK, QPSK, DBPSK, DQPSK, 16-QAM, 64-QAM, 256-QAM, 1024-QAM, 4096-QAM)
	Output Power	802.11ax: Max. 23dBm (per chain)
	Power Consumption	≤15W
	Receive Sensitivity	11ax : HE20 MCS0 < -82dBm / MCS11 < -52dBm HE40 MCS0 < -79dBm / MCS11 < -49dBm HE80 MCS0 < -76dBm / MCS11 < -46dBm
	Antenna Connector	4x U.FL Connectors
Physical Characteristics	Weight	Dimensions
	20g	60 (L) x 57 (W) x 4.1 (H) mm (Tolerance±0.15mm)
Environmental	Operating	Storage
	Temperature: -20°C to 70°C Humidity: 95% (non-condensing)	Temperature: -40°C to 90°C Humidity: 90% (non-condensing)
Safety Approval	RoHS/REACH Compliance	

PIN Definition

No.	Description	No.	Description	No.	Description	No.	Description	No.	Description
1	GND	2	3V3	3	NC	4	3V3	5	NC
6	PCIE_LED0	7	GND	8	UART_TXD	9	NC	10	UART_RXD
11	NC	12	NC	13	NC	14	NC	15	5V
16	PCIE_LED1	17	5V	18	GND	19	5V	20	NC
21	5V	22	NC	23	5V	24	Key	25	Key
26	Key	27	Key	28	Key	29	Key	30	Key
31	Key	32	NC	33	GND	34	NC	35	PCIE_RX0+
36	NC	37	PCIE_RX0-	38	PTA2_BT_PRI0	39	GND	40	PTA2_WL_ACT
41	PCIE_TX0+	42	PTA2_BT_ACT	43	PCIE_TX0-	44	PTA1_BT_PRI0	45	GND
46	PTA1_WL_ACT	47	PCIE_REFCLK+	48	PTA1_BT_ACT	49	PCIE_REFCLK-	50	NC
51	GND	52	PCIE_RST	53	PCIE_CLKREQ_N	54	NC	55	PCIE_WAKE_N
56	PCIE_WDIS_N	57	GND	58	NC	59	PCIE_RX1+	60	NC
61	PCIE_RX1-	62	NC	63	GND	64	NC	65	PCIE_TX1+
66	NC	67	PCIE_TX1-	68	NC	69	GND	70	NC
71	NC	72	3V3	73	NC	74	3V3	75	GND